Certificate of Location of Government Corner

ID#: 752404 **Description:** 1/4 SEC COR 24 25 75 **Date Set:** 8/13/2002 **County:** Olmsted

Section: 24 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in grass area north of KR-7 reservoir
Post w/sign 2' North
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes Karrick 40.00 set temp 1/4 section post west on true line between sec 24125 8° 36'. 40.00 set 1/4 sec post in mound with trench, pitts, charred stake and Osage Orange seeds NE&SW.

5-1880 T. Hunter unrecorded survey No.358, pg.111; Used the corner to set the 1/16 corner stone east and the limestone as the Center of section 24 and points N of the center. He set the 1/16 stone at 1314.4' midway and on line.

10-1968 John Kerr, Used the corner post to run the line north and found the limestones at the center of 24 and the 1/16 corner north.

6-9-1972 County Surveyor set CIM over 1 1/4"x2' pipe by the line and measure from the N & E.

8-13-2002 County Surveyor found CIM down 0.9' in good condition. Removed CIM and found 1 1/4" pipe down 2.5' in good condition. Removed pipe and set 6' telspar pipe w/Cast Iron Cap down 0.1'.