Certificate of Location of Government Corner

ID#: 752405 **Description:** SEC COR 23 24 25 26 75 **Date Set:** 8/22/96 **County:** Olmsted

Section: 24 **Township:** 107N **Range:** 15W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline of N-S twp road and in line with fence west
County highway disk in PP SE 69.82'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: Karrick; 80.00 set a post for section corner 23-24-25-26.Erected mound with trench, pits, charred stake and osage orange seeds at each angle.

4-1863 P.C. Compton, Pg.72 No.103; Shows 1/4 corner used to set center section 25.

5-1872 T. Hunter Bk.A pg.204; Found the old stake and set a stone 2"x8"x15" and a stake.

5-1880 T. Hunter, Unrecorded survey Og.111 No.358 old book. Used corner to set stone 1314.4 east.

8-1967 J. Kerr; Couldn't find the corner so he assumed a location and set a CIM.

Note: This is a correction of a corner. The correct corner as found by the County Surveyor in 1972 was 4.1' North and .3' east of the CIM that was in place. Removed all evidence of the old corner location.

6-12-1972 County surveyor found 2"x7" top limestone set in 5-1872 by Hunter. Removed CIM set 8-1967 and pipe below and reset same over stone found. Set 18" flaring metal plate over stone.

8-22-1996 county highway department set 1" square pipe with cap in centerline down 0.5'. RPs- spike and large disk in pp SE 69.82'.

6-27-2002 County Surveyor found 1" square pipe w/cap down 0.5' in good condition.

8-29-2006 County Surveyor found 1" square pipe w/cap down 0.9' in good condition.