Certificate of Location of Government Corner

ID#: 752504 **Description:** 1/4 SEC COR 25 36 75 **Date Set:** 8/28/74 **County:** Olmsted

Section: 25 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and in line with fences north and south
County Survey Disk in W side 2nd fence post N 41.68'
County Survey Disk in W side CP S 58.8'
This corner is located by GPS measurement

Corner History:

8-1854 Gov't Notes: Michael Karrick, Deputy Surveyor; Set a quarter post 40.00 chs west of East section corner 25-36 in mound with trench, pits, and charred stake and planted osage orange seeds NE and SW.

4-1863 P. Compton, Pg. 72 No. 3, used 1/4 cor. to set center 25.

9-1874 Thomas Hunter (Pg.260 No.259), County Surveyor, in survey plat shows a stone at this corner.

8-28-1974 County Surveyor dug with backhoe and found a stone in the center of the east-west road and approx. 1' west of fence line north. Placed a railroad spike on the east side of the stone and 2 railroad bolts beside the stone. Placed a CIM over all. This corner is 4.57' south of the line between the section corners.

8-12-2002 County Surveyor found CIM down 0.3' in good condition.