Certificate of Location of Government Corner

ID#: 752505 **Description:** SEC COR 25 26 35 36 75 **Date Set:** 8/12/91 **County:** Olmsted

Section: 25 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2 1/2' east of centerline of N-S twp road and 2 1/2' north of centerline of E-W twp road
Center large round steel CP SW 85.0'
Top center metal telephone cable post NW 122.4'
Natural blaze S side Maple or Elm NW 100'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: Karrick, 80.00 set post for corner to sections 25-26-35-36, erected mound with trench, pits, charred stake, and planted osage orange seeds at each angle.

6-1870 R. Perry, Pg.128 N0.160; Found stone monument set by Perry 7-9-1867.

4-1863 P.C. Compton Pg. 72 No. 103, show sec corner.

6-10-1968 John Kerr, REA substation; Set CIM over 5/8" iron centered on paint pail lid. RPs- Corner lies near centerline east-west road, corner lies 2-3' east of east edge traveled road north, Pepsi cap on east side power pole NNE 74.4, Old disc & nail on west side power pole SE 39.62, & teem cap on south side power pole WSW 139.0.

? County Surveyor found CIM down about 7". Reset CIM, all references on poles gone. New RPs- 85.0 SW to center large round steel corner REA fence on NE corner of fence, 12.24 NW to top center metal telephone cable post, & 100.0 Nwly to natural blaze on south side Maple or elm.

8-12-1991 County Surveyor set shorty CIM above other CIM.

8-12-2002 County Surveyor found CIM down 0.4' in good condition.