Certificate of Location of Government Corner

ID#: 752604 **Description:** 1/4 SEC COR 26 35 75 **Date Set:** 6/10/68 **County:** Olmsted

Section: 26 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and in line with fences north and south
Bolt in PP N 35.52'
Nail & disc in CP S 29.7'
Center number plate PP #22366 SW 65.9'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: Karrick; 40.00 set temperary 1/4 section post west on true line between sections 26 & 35. 40.00 set 1/4 section post in mound (V9°7') with trench, pits, charred stake, and planted osage orange seeds NE & SW.

1-1870 R. Perry, found stone placed in place of stake by Waldron.

5-1872 T. Hunter Pg.204 No.212, found stone Pg.128 as described. Set 1/16 west quarry stone 2x6x20 M & L 19.95 for line north to section corner stone 1316.7'.

6-10-1968 J. Kerr found stone, place CIM over original stone 2x8x14 which was lowered with 1"x10" pipe with smaller bent pipe inside below top 8" deep.

7-29-2002 County Surveyor found pk nail down 0.4'. Removed pk nail and found CIM down 1.1' in good condition.