Certificate of Location of Government Corner

ID#: 752605 **Description:** SEC COR 26 27 34 35 75 **Date Set:** 5/29/68 **County:** Olmsted

Section: 26 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and in line with fences north and south
Nail & disc in Oak fence post S 38.9'
Nail & disc in PP #22377 SE 80.9'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: 80.0 set post for corner to section 26-27-34-35. Erected mound with trench. Pits, charred stake & planted osage orange seeds at each angle.

6-1870 R. Perry Pg.128 No.160, Set stone 3 1/2x4 1/2x27.

5-1872 T. Hunter (Pg. 204 No. 212) found stone set in center of road

5-1885 T. Hunter Pg.396 No.386, Found stone Pg.128; 1/16 east set quarry stone 2x6x20 M & L 19.95. Corner used to set W 1/4 26.

5-29-1968 J. Kerr set CIM over original stone placed hub cap & sash weight. RPs-disc in pp 22377 SE 80.9, disc in oak corner post S 38.9.

7-25-2002 County Surveyor found 5/8" iron rod down 0.3' in good condition.

8-13-2002 County Surveyor removed 5/8" iron rod and found CIM down 1.2' in good condition.