Certificate of Location of Government Corner

ID#: 752706 **Description:** 1/4 SEC COR 27 28 75 **Date Set:** 4/6/76 **County:** Olmsted

Section: 27 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with E-W fence and 3' west of fence south
Post w/sign 2' North
This corner is located by GPS measurement

Corner History:

6-1854 Gov't Notes: Michael Karrick, Deputy Surveyor; North between sections 27 & 28. 40.00 chs set quarter section post. RPs- 6" oak S60°W130 links, 6" burr oak S21°E100 links

3-1871 Robert Perry (Pg.154 No.177), County Sureveyor found oringinal stake standing. Stake M&L 19.84 to center 27 (a stone in mound and pitts set) No. 145 Pg. 106.

5-1900 Robert Fraser (Pg. 680 No. 605) County Surveyor could not find stake. Ground plowed and drove a stake midway and on line between section corners away.

4-5-1976 County Surveyor found a 1/2" pipe near the corner post of 3 way fence.

4-6-1976 County Surveyor removed the pipe found and set a CIM over a 1/2" pipe as the corner .15' north and .50' east of the pipe location. There was a boulder too large to move at the exact midway and on line location so the final corner is set as closely as possible to that location.

5-31-2002 County Surveyor found CIM down 0.5' in good condition.