Certificate of Location of Government Corner

ID#: 753005 **Description:** W SEC COR 30 31 75 **Date Set:** 8/14/70 **County:** Olmsted

Section: 30 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and 1 1/2' S of fence east
Hard nail in S side 12" Oak CP E 36.0'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes Karrick 80.00 set post and drove charred stake 10" long to sections 25-30-31-36, built mound planted SE Osage Orange seeds NE Apple seeds.

5-1871 R. Perry found stone

6-23-1970 County Surveyor meas from NE 31 west found stone at 1/16 at 1316.57, found fence north a good fence at 2632.6 set stub of old steel post south of huge corner post which lines main fences E-W-N con't to fence south at 11/6 west of N 1/4 31 found exact wires 4-1/2 south of cor post 1317.0, con't to centerline road set 1/2" rod in line fence east at 1248.72 record meas. Meas south to rod set as 1/16 1320.48 referenced. Meas rod to exact centerline RR on line 1498.39 referenced. Meas rod to nail in centerline paving set on computed 1 mile line which is 3.8' east of direct mile line (this nail could be changed).

8-14-1970 County Surveyor used tractor, found corner easily a very large sandy limestone 30" x 12 x 10" triangular shaped about 2' deep. Removed stone dug hole deeper, placed 3/4" x 14" pipe and 30" stone on rod with CIM above 5" deep. Corner 1.3' south and .67' west of iron (removed). Pepsi cap in unmarked power pole SW side SSE 96.6'.

8-18-1970 County Surveyor, 1/16 south now 1/2 x 3' rod at 1320.67 centerline railroad 1497.13 a 16" 1/2" pipe.

5-20-2002 County Surveyor found CIM down 0.5' in good condition.