# Certificate of Location of Government Corner

**ID#:** 753009 **Description:** SEC CEN 30 75 **Date Set:** 5/19/2004 **County:** Olmsted

**Section:** 30 **Township:** 107N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

County Surveyor recommends using the computed intersection of quarter lines for the center of section.

5/8" pipe w/cap RLS #41814

**Reference Ties:**

The corner falls 1' south of centerline of east-west twp road (13TH ST NW), in line with fence north, and 10' west of fence south
The monument is down 0.3'
This corner is located by GPS measurement

**Corner History:**

5-15-1871 Robert Perry, County Surveyor, (Book A, Pages 162-166, Survey No. 185) set temporary stake at intersecting quarter lines. 1/16th South set temporary stake midway and on line at 20.01-3/4 chains (1321.16') to South 1/4. 1/16th East set temporary stake midway and on line at 19.99 chains (1319.34') to East 1/4. 1/16th Center of SE 1/4 set 4"x10"x20" stone.

4-17-1990 Vince Fangman used computed center at intersecting quarter lines.

7-29-2002 McGhie & Betts, Inc. used computed center at intersecting quarter lines.

5-19-2004 Massey Land Surveying set 5/8" pipe w/cap RLS #41814 at intersecting quarter lines.

1-31-2006 County Survey Crew found 5/8" pipe w/cap RLS #41814 down 0.3' in good condition and measured its position using GPS.

2-11-2008 Fangman Land Surveying used computed center at intersecting quarter lines.

7-17-2009 Joel Thoreson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the 5/8" pipe w/cap, as located by GPS in 2006, falls 0.03' north and 0.01' west of the computed center.