Certificate of Location of Government Corner

ID#: 753606 **Description:** 1/4 SEC COR 35 36 75 **Date Set:** 8/14/2002 **County:** Olmsted

Section: 36 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls on top of berm and 1 1/2' east of N-S PP line
Disc in PP NNE 114.1'
Nail & disc in PP SSE 152.1'
Post w/sign 2' North
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: 40.0 set 1/4 post in mound with trench, pits, charred stake, and planted osage orange seeds NE & SW

No records

6-10-1968 J. Kerr set CIM 2' below surface in old road, 1/2 " rod below CIM. RPs- Disc in power pole NNE 114.1, disc in power pole SSE 152.1', and point under pole line E 24.5'.

8-27-1974 County Surveyor dug with the backhoe 12' + south of J.Kerr corner to 6' north and from the west side of the monu. over to 1± west of centerline road, found nothing. Measured 402.85 to centerline of track. Hunters rail records 391.0'

8-14-2002 County Surveyor found 5/8" rerod at surface in good condition inside 4" casing. Removed rerod and found CIM down 2.3' in good condition. Removed CIM and found 1/2" rerod down 4' in good condition. Set 6' telspar pipe w/Cast Iron Cap at surface over 1/2" rerod.