Certificate of Location of Government Corner

ID#: 803105 **Description:** SW SEC COR 31 80 **Date Set:** **County:** Winona

Section: 31 **Township:** 108N **Range:** 10W **Monument Description:** Cut stone monument

Reference Ties:

The stone is up 0.4'
County Survey Disk in NW side 8" blazed Hackberry NE 26.21'
County Survey Disk in N side blazed Red Oak WNW 6.33'
County Survey Disk in W side 3 1/2" blazed White Oak SE 20.23'
Post with sign 1.5' east

Corner History:

1853 Gov't Notes E. Norris, Deputy Surveyor North between sections 1 and 6. 80.00 chs. Set post for corner to Townships 107 and 108 North of Ranges 10 and 11 West Black Oak 14 in. N28ºW 158 lks. White Oak 14 in. S17ºW 45 lks. Black Oak 12 in. S10ºE 70 lks. White Oak 13 in. N42 1/2ºE 50 lks.

1875 State law required monuments to be set at township corners. Thomas Hunter, County Surveyor, placed stone monuments as required although there is no survey notes documenting this particular corner.

6-30-1977 Olmsted County Surveyor found a 10"x10" cut stone monument up 6". Drove a 1/2" iron (up 1') on the North side of the stone and a 1/2" pipe (up 1') on the South side of the stone.

4-5-2010 Olmsted County survey crew found 10"x10" cut stone monument up 0.4' in good condition.