Certificate of Location of Government Corner

ID#: 813404 **Description:** S 1/4 SEC COR 34 81 **Date Set:** 9/13/1977 **County:** Wabasha

Section: 34 **Township:** 108N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument at surface
The corner falls 2' south of E-W fence and 2' east of fence north
County Survey Disk in W side blazed White Oak S6°E 43.93'
County Survey Disk in E side blazed White Oak S 52°W 24.54'
County Survey Disk in E side blazed 7" White Oak N 2°W 27.69'
County Survey Disk in W side blazed 12" Hackberry N 14°W 19.01'
Blazed 16" White Oak NE 5'
Sign on N side of 24" Oak tree
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes Set post for 1/4 sec corner Black Oak 12" S 81°W 314 links 207.24. Black Oak 10" N 75°W 364 links 240.24. 45.00 chains enter dry creek bottom bears SE 50.20 chains whitewater creek 50 links wide runs SE.

7-13-1977 Olmsted County Surveyor found 1/2" pipe (up 1') in line with the fence S (E-W fence not distinct). Pipe 4.61 S and .58 E of M&L to final corner.

9-13-1977 Olmsted County Surveyor set Cast Iron Cap on telspar pipe in place of stone found. Stone 9" x 9" x 12" coming to a point on top found 2' S of the E-W fence and 2' east of the fence north. Set the stone along side the monument. Set square pipe up 2' 1-1/2' SE of the corner. Corner .55 E and .55 S of T.N. RP's: Spike and CSD in W side blazed White Oak S 6°E 43.93. Spike and CSD in E side blazed 8" White Oak S 52°W 24.54. Spike and CSD in E side blazed 7" White Oak N 2°W 27.69. Spike and CSD W side blazed 12" Hackberry N 14°W 19.01. Blazed 16" White Oak NE 5'.

3-16-2010 County Survey Crew found CIC/p2 up 0.5' in good condition.

4-5-2010 County Survey Crew found CIC/p2 up 0.5' in good condition.

4-13-2010 County Survey Crew found CIC/p2 up 0.5' in good conditioin. Pounded monument down flush w/surface.