Certificate of Location of Government Corner

ID#: 813405 **Description:** S SEC COR 33 34 81 **Date Set:** 7/14/1977 **County:** Wabasha

Section: 34 **Township:** 108N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument falls on SW corner of woods.
Sign with post 2' East
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes: Set post and drove charred stake, built mound with trench.

12-1891 Thos. Fraser (P.467 No.449) found fence post set by Mr. A Ferrier in center of original mound when stake was standing plain. 1/16 cor south set stake on line and prop dist line overran 56 1/4 lks meas from corner S 20.25 then 20.28-1/4 to cor between 3-4 a stake reset by B trees. 1/16 center NE 1/4 4 set stake M&L 20.16-1/4 on EW 1/6 line. 1/16 cor on N-S 1/4 line between N 1/4 4 and center found stone and stake set by Mr. Basturck a surveyor from Wabasha County set years ago when corners in place. All corners gone in west half section 4. Accepted stone and stake as corner for work at hand land very rough and brusky nearly impossible to work in.

7-14-1977 Olmsted County Surveyor accepted the corner post as per Tom Fraser survey No.449. Set a cast iron cap on telspar pipe as the corner on the SE side of the corner post to fences N and east.

12-17-2009 County survey crew found cast iron cap on telspar pipe down 0.4' in good condition.