Certificate of Location of Government Corner

ID#: 813605 **Description:** S SEC COR 35 36 81 **Date Set:** 6/28/1977 **County:** Wabasha

Section: 36 **Township:** 108N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' east of centerline of main road north and 15' west of centerline of driveway on curve
Sign on post 5.5' West
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes: Set post for corner line tree 12" Black Oak 5.71 chains south. BT's: Burr Oak 14" N 74° E 97 links. Black Oak 12" N 4° W 315 links. Burr Oak 8" S 80° E 127 links. Black Oak 14" S 80° W 112 links.

10-11-1900 W. Fraser (P.692-8 No.615) found stone at corner and stumps SE and SW B trees which checked correct. New B tree 8" Black Oak S 16-1/2° W 33 lks. Drove stake by side of stone meas west to 1/4 cor stone 39.78 (2625.48) which proved 15 (9.9') links too far east for midway and 6 (3.96) links too far south for line. Accepted 1/4 cor and section corners as true corners but not stones west of 1/4 corner.

6-28-1977 Olmsted County Surveyor found 4" x 7" x 14" limestone with 3/4" x 18" bolt on E side of it. Top stone down 2-1/2' in sh. slope set bolt back on E side and placed lots of junk around the stone with 20" CIM above it. Corner ± 7' east of drill steel shaft which we removed. RP's: Spike in telephone pole NNW 27.55. 60p spike in S side of 48" Willow tree west 11.1 centerline of driveway on curve east 15'. Corner lines 2' east of centerline main road to north.

12-17-2009 County survey crew found cast iron monument down 0.6' in good condition