Certificate of Location of Government Corner

ID#: 820605 **Description:** W SEC COR 6 7 82 **Date Set:** 9/1999 **County:** Wabasha

Section: 06 **Township:** 108N **Range:** 12W **Monument Description:** 1/2" pipe

Reference Ties:

The corner falls in centerline of N-S twp road, in centerline of twp road east and 4' north of centerline of twp road west
County Survey Disk in N side PP #47101 SE 59.42'
County Survey Disk in N side PP #47102 WSW 158.06'
This corner is located by GPS measurement

Corner History:

1853 John Ball; 80.0 set post and drove charred stake cor. To sections 1,6,7,&12. Built mound with trench per instructions. Planted osage orange SE and apple seed NE.

9-1999 Johnson & Scofield, Inc. excavated with a backhoe at the intersection of the cenerline of a north-south Township Road and the centerline of a Township Road running east and a Township Road running West. The Township Road running east is 4 feet, more or less, north of the Township Road running west. The excavation was 12 feet by 12 feet by 5 feet deep. The original road bed was found at 2 feet. The original clay was found at 4 feet. An additional 2 feet was dug into clay and nothing was found. The intersection of the centerline of the north-south Township Road with the centerline of the Township Road running east is closer to a proportionate measure along the west line of Section 6 and 7 and was accepted as the best perpetuation of the Original Public Land Survey Corner. Two 1 inch by 18 inch iron pipes were placed one on top of the other, with a 2 inch cast iron cap, stamped "Survey Marker", affixed to the top.

7-12-2007 Olmsted County Surveyor found pipe with broken cap stamped survey marker down 0.6', removed cap and found pipe in good condition. Set CSD w/concrete nail in N side of PP #47101 SE 59.42' and CSD w/concrete nail in N side of PP #47102 WSW 158.06'.