Certificate of Location of Government Corner

ID#: 820606 **Description:** W 1/4 SEC COR 6 82 **Date Set:** 9/1999 **County:** Wabasha

Section: 06 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Cap on 1" pipe

Reference Ties:

The corner falls in centerline of N-S twp road, in line with fence west and 3' south of fence east
County Survey Disk in W side PP #24449 SSE 98.46'
This corner is located by GPS measurement

Corner History:

1853 John Ball; 40.0 set post and drove charred stake for quarter section corner. Built mound with trench per instructions. Plnated SE osage orange, NE apple seed.

9-1999 Johnson & Scofield, Inc. searched for corner with magnetic locator at the intersection of centerline of the north-south Township Road and fence line east and fence line west. Nothing was found. The fence line west falls 3 fee, more or less, south of the fence line east. No excavation was made because the Township Road is in a cut section. The intersection of the fence line running west with the centerline of the north-south Township Road is closer to a proportionate measure along the west line of Section 6 and was accepted as the best perpetuation of the Original Public Land Survey Corner. Two 1 inch by 18 inch iron pipes were placed one on top of the other, with a 2 inch diameter cast iron cap, stamped "Survey Marker", affixed to the top.

7-12-2007 Olmsted County Surveyor found pipe w/cap with "X" and stamped survey marker down 0.6' in good condition. Set CSD w/concrete nail in W side of PP #24449 SSE 98.46'.