Certificate of Location of Government Corner

ID#: 820706 **Description:** W 1/4 SEC COR 7 82 **Date Set:** 9/1999 **County:** Wabasha

Section: 07 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Cap on pipe

Reference Ties:

The corner falls in centerline of N-S twp road and in line with fences east and west
County Survey Disk in E side PP #24438 NNW 85.29'
County Survey Disk in E side PP #44110 SSW 136.25'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes: John Ball, 40.00 set post and drove charred stake for quarter sec. cor. Built mound with trench per instructions. Planted SE Osage Orange NE Apple seed.

9-1999 Johnson & Scofield, Inc. excavated with a backhoe at the intersection of the centerline of a north-south Township Road and a fence line running east and a fence line running west. The excavation was 10 feet by 10 feet to a depth of 5 feet, which reached 3 feet into natural soil. Nothing was found. The intersection of the centerline of the north-south Township Road with the fence line running east and a fence line running west was accepted as the best perpetuation of the Original Public Land Survey Corner and was substatiated by measurements made to the northwest corner and southwest corner of Section 7. Two 1 inch by 18 inch iron pipes were placed one on top of the other, with a 2 inch diameter cast iron cap, stamped "Survey Marker", affixed to the top.

7-12-2007 Olmsted County Surveyor found pipe w/raised cap stamped survey marker down 0.7' in good condition. Set CSD w/concrete nail in E side of PP #24438 NW 85.29' and CSD w/concrete nail in E side of PP #44110 SSW 136.25'.