Certificate of Location of Government Corner

ID#: 821805 **Description:** W SEC COR 18 19 82 **Date Set:** 8/2/1983 **County:** Wabasha

Section: 18 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.5'
The corner falls 3' east of centerline of N-S twp road, in line with fence west and 20' south of driveway east.
County Survey Disk in CP W 30.57'
County Survey Disk in PP #32223 SSE 73.59'
County Survey Disk in PP #32222 SSW 79.62'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes John Ball, Deputy Surveyor North between sections 19 and 24. 80.00 chs. Set post and drove charred stake for corner to sections 13,18,19 & 24. Built mound with trench per instructions. Planted S.E. Osage orange seed, N.E. Apple seed.

11-1877 Thomas Hunter, County Surveyor, (Book A, Page 323, No. 317, and old Fieldbook 5, Page 26) "Found the remains of old stake in center of road in line of old fence running west and claimed by old settlers to be where the original corner stood. Set stone in its place 24x5x5 with shoe at lower end." He used the corner to set the 1/16 west, a stake, midway (19.97 chs.) and on line to 1/4 Cor. 13-24, and to set the E. 1/4 Cor. 24 midway (40.01 chs.) to the E. Sec. Cor. 24-25.

7-26-1983 Olmsted County Surveyor dug for corner and found a 5"x5" topped limestone down 1.8' in road. The top 1' of the stone was broke off, but set it back exactly. Drove a 1 1/4" pipe on the south side of the stone, a 1/2" pipe on the north side, a bridge bolt on the east side, and a 120d spike on the west side. The corner is in the centerline of the N-S road and is in line with the fence running west.

8-2-1983 Olmsted County Surveyor set a Cast Iron Monument over the stone found. Measured south 2639.73' to stone found at the E 1/4 Cor. 24, and west 2635.40' to 1/4 Cor. 13-24 as set this survey.

9-7-2010 Olmsted County survey crew found CIM in good condition