Certificate of Location of Government Corner

ID#: 821806 **Description:** W 1/4 SEC COR 18 82 **Date Set:** 9/1999 **County:** Wabasha

Section: 18 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Cap on 1" pipe

Reference Ties:

The monument is down 0.6'
The corner falls in centerline of N-S twp road and in line with fence west and in centerline of driveway east
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes: John Ball, 30.00 enter scattering timber bears NW. 40.00' set post for quarter section corner. Burr Oak 6 S35°E 147 links. Bur Oak 6 S6°W 288 links. 50.00' enter prairie bears NE.

9-1999 Johnson & Scofield, Inc. found a spike at the intersection of a north-south Township Road with a fence line running west. An area 12 feet by 8 feet was excavated with a backhoe to a depth of 4.5 feet, which reached 2 feet into natural soil. Nothing was found. The intersection of the centerline of the north-south Township Road with the fence line running west was accepted as the best perpetuation of the Original Public Land Survey Corner and was substantiated by measurements made to the northwest corner and the southwest corner of Section 18. Two 1 inch by 18 inch iron pipes were placed one on top of the other, with a 2 inch diameter cast iron cap, stamped "Survey Marker", affixed to the top.

9-7-2010 Olmsted County survey crew found CIC in good condition