Certificate of Location of Government Corner

ID#: 821906 **Description:** W 1/4 SEC COR 19 82 **Date Set:** 8/2/1983 **County:** Wabasha

Section: 19 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1-1/2' west of centerline of north-south township road (80th Ave NE) and 1-1/2' south of fence west
The monument is down 0.5'
This corner is located by GPS measurement

Corner History:

10-18-1853 John Ball, Deputy Surveyor, measured north 40.00 chains between Sections 24 and 19. Set post and drove charred stake for quarter section corner. Built mound with trench per instructions. Planted Osage Orange seed SE and Apple seed NE.

11-8-1877 Thomas Hunter, Olmsted County Surveyor, (Book A, Page 323, Survey No. 317), "1/4 post missing and could not be found by the most careful search. We therefore measured the line carefully from G (SE Section Corner 24) to A (NE Section Corner 24) and set a stone 13"x7"x2" midway between and midway between the road fences which are here 4 rods apart." Stone falls within one link (0.66') of fence east.

7-26-1983 Olmsted County Survey Crew dug and found 3"x8"x16" limestone down 0.5' in good condition. Removed stone and set 1" pipe at stone location and set stone on south side of pipe. The corner falls 1-1/2' west of centerline of north-south township road, 1-1/2' north of fence east and in line with old fence ridge west.

8-2-1983 Olmsted County Survey Crew set Cast Iron Monument over the pipe.

9-7-2010 Olmsted County Survey Crew found Cast Iron Monument down 0.5' in good condition and measured its position using GPS.