Certificate of Location of Government Corner

ID#: 823005 **Description:** W SEC COR 30 31 82 **Date Set:** 6/9/2008 **County:** Wabasha

Section: 30 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' south of centerline of E-W twp road and 3' west of centerline of N-S twp road
County highway disk in PP #19822 NE 50.15'
County Survey Disk in NW side of PP #19821 NW 59.38'

Corner History:

9-1853 Gov't Notes: John Ball, 80.00 set post and drove charred stake corner to sections 25, 30, 31 and 36. Built mound with trench per instructions. Planted SE Osage Orange NE Apple seed.

11-1886 T. Hunter P.416 No.405 corner gone, meas NE 25 to SE 36 divided midway 80.02, meas south to 1/4 cor 40.01. Meas N 1/4 31 108-12 west to NW 35 197.02 short 22 links, meas east 37.26 west 39.98. Set stone and drove iron rod by its side and corner.

7-1898 W. Fraser P.639 No.575 found all corners set above in SW 1/4 36, did not use any corners on east side S 36.

1946 Olmsted county highway department Book 149 page 48 found 4x8x20 limestone on edge. Set 1/2" rod and horse shoe above.

5-22-1965 J. Kerr found the east common corner sections 25 and 36 Farmington Township which was evidenced by 4" x 8" x 24" limestone with iron above it. Placed cast iron monument above stone.

9-12-1972 Olmsted County Surveyor visited corner to run line and meas west found CIM tipped north badly well over 15" on tip with at least 12" hard rocky fill over area by new grade. Dug out CIM and entire area down to original stone checked by 3 remaining RP's: 50.2' NE to disc on NW side PP #19822, 59.4' NW to disc on SW side PP #19821, 28.2' NE to punch hole in top center N end 15" culv, 27.72' SE to punch hole in top center S end 15" culv.

3-28-2008 Olmsted County Surveyor found CIM down 1.5' leaning north.

6-9-2008 Olmsted County Surveyor found CIM down 1.5' leaning North. Took local ties and removed. Found stone down 3.5' in good condition. Set 3' telspar pipe w/cast iron cap down 0.5' at stone location.