Certificate of Location of Government Corner

ID#: 823006 **Description:** W 1/4 SEC COR 30 82 **Date Set:** 6/11/2008 **County:** Wabasha

Section: 30 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 4' east of centerline of north-south township road (80th Ave NE) and in line with fence west
The monument is down 0.5'
Hub in S side PP #24411 W 49.66'
County Survey Disc in N side PP #24411 W 49.68'
This corner is located by GPS measurement

Corner History:

10-18-1853 John Ball, Deputy Surveyor, measured north 40.00 chains between Sections 25 and 30. Set post and drove charred stake for quarter section corner. Built mound with trench per instructions. Planted Osage Orange SE and Apple seed NE.

5-7-1946 Olmsted County Highway Department, (CHD Book 149, Page 48), found 6"x8"x24" limestone on edge. RPs - Steel fence post W 73.2', Spike in fence post E 62.0'.

5-22-1965 John Kerr, Olmsted County Surveyor, found limestone. Set Cast Iron Monument over stone. The corner falls 2' east of centerline of north-south township road, in line with fence west and 2' north of fence east. RPs - Spike in fence post E 62.25', Nail in hub on power pole W 49.2'.

6-14-1983 Olmsted County Survey Crew found Cast Iron Monument.

3-28-2008 Olmsted County Survey Crew found Cast Iron Monument down 0.9' leaning north.

6-11-2008 Olmsted County Survey Crew found Cast Iron Monument down 0.9' leaning north. Removed Cast Iron Monument along with broken stone pieces on north and south sides of Cast Iron Monument and found 1/2" rerod down 2.8' in good condition. Removed 1/2" rerod and set 6' telspar pipe w/cast iron cap down 0.5' at 1/2" rerod location and measured its position using GPS. The corner falls 4' east of centerline of north-south township road. RPs -Hub in S side PP #24411 W 49.66', County Survey Disc in N side PP #24411 W 49.68'.