Certificate of Location of Government Corner

ID#: 823106 **Description:** W 1/4 SEC COR 31 82 **Date Set:** 6/6/2008 **County:** Wabasha

Section: 31 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5' west of centerline of N-S twp road and in line with fence east
County highway disk in PP #24398 W 43.65'
Center concrete CP W 30.2'
1/2" steel rod under fence E 50.0'

Corner History:

10-1853 Gov't Notes: John Ball, Deputy Surveyor at 40.00 chs. Set post and drove charred stake for quarter section corner. Built mound with trnch per instructions. Planted Osage Orange seeds SE and Apple seeds NE of corner.

11-1886 T. Hunter (Pg. 416 No. 405). Corner missing no evidence could be found. Set stone 4" x 6" x 18" with iron by side M&L 40.01 chs.

6-23-1966 J. Kerr found stone as recorded in size with wood stake (no iron). Set CIM over stone and 1 1/2" x 10" conduit.

10-2-1972 Olmsted County Surveyor found monument in good condition.

4-3-2008 Olmsted County Surveyor found CIM down 1.3' in good condition.

6-6-2008 Olmsted County Surveyor found CIM down 1.3' in good condition. Took local ties and removed. Found stone w/iron beside down 3.0' in good condition and matching local ties. Set CIM down 0.5' at old CIM location.