Certificate of Location of Government Corner

ID#: 823204 **Description:** S 1/4 SEC COR 32 82 **Date Set:** 11/4/1974 **County:** Wabasha

Section: 32 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is at the surface
The corner falls 12' west of CP to fence north and west.
Post with sign, north 2'.
This corner is located by GPS measurement.

Corner History:

1853 Gov't Notes: John Ball, Deputy Surveyor west between sections 5 and 32. 40.00 chs. Set post and drove charred stake. Built mound with trench. Planted osage orange SE and apple NE.

11-1891 Tom Fraser (P. 465 No. 447), County Surveyor, found large post avered by a Mr. Dickerman and his father owning lands north and east as set on the edge of original stake. Set 1/16 west.

11-4-1974 Olmsted County Surveyor found stake on measure from west by doubling over 1/16 west (a stone found 11-1-1974). The stake falls 12' west of the corner post of the fence running north. Distance and line from NE Cor. Sec. 5 over 1/16 west of NE Cor. Sec. 5 checked well. Set CIM over stake found.

10-1-2010 County survey crew found CIM leaning north. Moved the CIM to a plumb position before taking a GPS measurement.