Certificate of Location of Government Corner

ID#: 823305 **Description:** S SEC COR 32 33 82 **Date Set:** 3/13/2009 **County:** Wabasha

Section: 33 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

This corner falls 1' west of fence north
Sign on CP 1' NE
This corner is located by GPS reference stations "BDO A & B"

Corner History:

Gov't Notes Jones 1853 80.00 set section corner post of sections west of N 3-4. Made mound with trench and deposited seeds.

11-1891 T. Fraser P 465 No. 447 corner not used in this survey evidently. Caption shows stone as corner. Also stone west 10.03-3/4 then west to 1/16 corner a boulder stone 10.03-3/4 set M & L as 1/16 corner, then west 20.07-1/2 to N 1/4 5

10-1894 W. Fraser P 553 No. 510 found boulder tone placed by Wabasha County Surveyor 1/16 east set boulder stone 19.98 M & L to stone N-1/4 4.

11-4-1974 Olmsted County Surveyor found stone boulder on south side of corner post 3' south of corner post.

7-24-1991 Olmsted County Surveyor found stone foundd in 1894 by W. F. and County Surveyor in 1974. Dug out stone which measured 12x20x28 running to a point on top with flare to 20" in middle. Found nothing below stone, moved to the side and set cast iron cap on telspar pipe in its place. Set sign & post 1.0' north.

12-11-2006 Olmsted County Surveyor visited area of corner and found 8" diameter fence post near corner location.

3-13-2009 Olmsted County Surveyor set a 4' telspar pipe w/CIC at surface from GPS coordinates.