Certificate of Location of Government Corner

ID#: 823405 **Description:** S SEC COR 33 34 82 **Date Set:** 6/2/1986 **County:** Wabasha

Section: 34 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2 1/2' east of N-S fence
20d spike in 9" Box Elder NE 4.42'
20d spike in 8" Box Elder SE 4.62'
Post w/sign 1' east
This corner is located by GPS reference stations "Bench Seat A & B"

Corner History:

Gov't Notes Jones 1853 80.00 set section post. made mound with trench. one pit, 8 lks south. Bur Oak 10" N 37 W195 lks.

5-1890 T.Fraser P. 441 No. 427 corner gone, B. trees gone. old fences ran to old post note with small pine stake south of it. Also Oak tree 2' southewesterly claimed by Mr. Dickerman as there when fences set from original corner. Mr. Dickerman to set stone after survey.

10-1894 W. Fraser P. 553 No. 510 found stone placed by Mr. Dickerman in place of stake as instructed P. 441 no meas.

8-15-1972 Survey crew of Kassler company report easily finding vertical limestone by corner post. Corner left as found - accepted information as true and accurate.

6- 2 & 3-1986 Tom Ferguson found 2-1/2" x 6" x 30" stone .8' below ground surface at intersection of N-S-E fence lines and placed a CIM on E side of stone .7' down -- center of monument is .21' east of center of stone 20d spike in 9" box elder NE 4.42' CIM 2-1/2 E N-S fence 20d spike in 8" box elder SE 4.62 / 2630.18 N. to 1/4 Cor. 33-34

4-12-1990 Olmsted County Surveyor agreed with Wabasha County Surveyor to use C.I.M. as corner set by Tom beside stone if stone in fact was corner.

7-24-1991 Olmsted County Surveyor found CIM set by Tom Ferguson in 1986, also box elder ties in good shape. Set sign and post 1' east of CIM.

12-6-2006 Olmsted County Surveyor found CIM down 0.5' in good condition.