Certificate of Location of Government Corner

ID#: 823504 **Description:** S 1/4 SEC COR 35 82 **Date Set:** 9/1999 **County:** Wabasha

Section: 35 **Township:** 108N **Range:** 12W **Monument Description:** Wabasha County Monument

Reference Ties:

The corner falls 7 1/2' south of centerline of E-W twp road and 12' west of fence south
County Survey Disk in top of end fence post S 44.50'
This corner is located by GPS measurement

Corner History:

Gov't Notes Jones 1553 Set 1/4 Section post M & L 40 chains 5250 for mile drove charred stake built mount with trench.

10-1889 Thomas Fraser P436 No. 423 found stone set by Hunter in unrecrorded survey. 1/16 west 2 corners here, one set by Hunter and one by another surveyor. (No meas. or further comment.

1972 Olmsted County Surveyor, corner very doubtful road curves north into Wabasha County east of corner of west of corner straign road between supposed on County line but could be anywhere. No meas. in any direction or desc. of stone or if on line between section corners. much work and research before corner could be set.

3-1977 Yaggy Assoc. (Don B.) E. Trav. on N. Line of Sec. 2 - Total dist. 5246.02', he will use M & L point at this 1/4 Cor. which fits N-S fences at this 1/4 cor. - line fell +- 7'N of centerline E-W Road; because of Large hills which road goes around both E & W of this area. Apparently nothing set as 1/4 cor. 7-6-77 Dug with backhoe in dep fill. Dug on M & L point by Yaggy's Dug 11' deep. Just coming into black dirt. Could not reach very well and side walk were falling in hole so abandoned.

7-11-1980 Olmsted County Surveyor, (1980 Remon. Book) Dug from center of road (which Yaggy's report is 7-1/2' South of line) North for 12', East for 3 to 4 feet and west for 5 to 6' by 12' deep to clay. The was 11' of sand fill over the natural ground. We found only one mark that was a possible corner location. This mark was about 9" diameter was filled with the sandfill and went into clay. There were no wood pieces to indicate a point was set here. It could have been where the stone had stood or where someone dug down when we attempted to dig for this corner in 1977.

7-16-1980 Olmsted County Surveyor, (1980 Remon. Bk) N1/4 Cor. 2: Set spike in road over spot found 7-11-1980 from local reference points and took R.P.'s. CSD in top of end fence part of fence south- south 44.50 Corner of westerly concrete headwall of culvert East 192.80 Corner 8' North of Center of road.
See Vertical File - Survey Data Range 12 for Yaggy Survey in Section 35, 108-12.

9-1999 Johnson & Scofield set corner at lost position after conversation with the Olmsted County Surveyor. Set two 1 inch by 18 inch iron pipes, one on top of the other with a 2" diameter cast iron cap stamped "Survey Marker".

8-4-2003 Olmsted County survey crew found Wabasha County CIM down 0.6' in good condition.