Certificate of Location of Government Corner

ID#: 823505 **Description:** S SEC COR 34 35 82 **Date Set:** 9/3/2009 **County:** Wabasha

Section: 35 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.4'
This corner falls 7' south of centerline of E-W twp road and 53' east of common field line north
County Survey Disk in W side PP #33571 SSE 42.10'
Nail in pole SW 40.92'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor. West on north boundary of section 2. 80.00 chs. Set section corner post. Built mound with trench and pit 8 lks. South. Burr Oak 10 in. S37°E 37 1/2 lks.

10-1889 Thomas Fraser (P. 436 No. 423), County Surveyor, found boulder placed and used by Hunter where gov't stake stood.

5-1890 Fraser (P. 441 No. 427) found stone P. 436 and tested SW (not original) bearing tree stump. Measured south to 1/4 corner 2-3 and then to Sec. corner 2-3-10-11.

8-17-1972 Olmsted County Surveyor ran by electronic traverse comp. From Sec. corner 2-3-10-11 (a stone and iron found) over 1/4 corner 2-3 (a stone found) and set a point at prorated Thomas Fraser (Survey No. 427) measurement from 1/2 corner 2-3.

7-9-1973 Olmsted County Surveyor set a 3/4 length CIM over a railroad spike at point established in 1972.

2-10-2000 Olmsted County Surveyor found CIM w/head broken off in good condition.

9-2-2009 Olmsted County Surveyor found CIM down 0.7' w/head broken off, took local ties and removed. Found railroad spike down 1.8' in good condition, ties matched.

9-3-2009 Olmsted County Surveyor set 16" CIM over RR spike down 0.4'.

7-6-2011 County survey crew found CIM in good condition