Certificate of Location of Government Corner

ID#: 823604 **Description:** S 1/4 SEC COR 36 82 **Date Set:** 7/5/2011 **County:** Wabasha

Section: 36 **Township:** 108N **Range:** 12W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The monument is down 0.6'
The corner falls 3' south of centerline of E-W twp road and 1' west of fence south
This corner is located by GPS measurement

Corner History:

Gov't Notes Williams Jones 1853 40.00 set 1/4 sect. post in M & L 40 chs. 2640' built mound with trench Planted Osage Orange seeds S.E and apple seed N.E.

6-1902 Robt Fraser unrecorded survey in old record field book without front cover No. 10 P 42 at "B" found stone which was on line of fences and in the middle of road. A Mr. Evans said was correct, left as found.

7-6-1973 Olmsted County Surveyor dug with tractor without any research by line or meas. in line fences N & S and center road. Found positive limestone not too long with top of stone broken loose. Set CIM over iron with stone found on west side.

7-5-2011 County survey crew found cast iron monument down 0.7' with top broken. Also found stone with top broken south of the CIM. Removed the CIM and stone and searched for but did not find an iron below the CIM as mentioned in 7-6-1973. Replaced the broken CIM with a 4' telspar pipe with cast iron cap down 0.6'.