Certificate of Location of Government Corner

ID#: 823605 **Description:** S SEC COR 35 36 82 **Date Set:** 7/9/1973 **County:** Wabasha

Section: 36 **Township:** 108N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 8' west of centerline of N-S twp road
4th staple in ground wire under PP number plate #32859 in SW side PP SE 44.5'
Conc nail in SE side PP #33130 SW 37.66'
SE corner bottom of siding of new house NW 145.85'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes Jones Set section post at 80 chains from east 5280' Bur oak 12 in N 68 W 123 lks dug trench. Bur Oak 10 in. S 32 E 200 lks. dug trench. Bur Oak 12 in. N 9-1/2 E 297 lks dug trench.

10-1889 Thos. Fraser P436 No 423 found stick of stove wood placed by Hunter on unrecorded survey on county line. 2659.64 -Meas. south 40.29 3/4 to boulder set proportionate measure. - figured proportions 20.32-1/2 and 19.97-1/4 3 times

7-6-1973 Olmsted County Surveyor set a point at prorated T. Fraser location.

7-9-1973 Olmsted County Surveyor dug area but found nothing. Set CIM over iron rod at point established 7-6-1973.

2-10-2000 Olmsted County Surveyor found CIM in good condition.