Certificate of Location of Government Corner

ID#: 830104 **Description:** 1/4 SEC COR 1 12 83 **Date Set:** 7/9/2012 **County:** Olmsted

Section: 01 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is down 0.7'
The corner falls in centerline of E-W township road and in line with fence south.
This corner is located by GPS reference stations "Cowboy A & B"

Corner History:

1854 William Yerby; 39.96 set a quarter section post in mound of earth & sod. Deposited charcoal, made trench, pits , and planted osage orange seeds N & S.

7-12-2007 County survey crew visited area, did not find anything.

10-4-2011 County survey crew dug for the 1854 quarter section post. The excavation was 12' x 12' with a depth of 2.5'. The excavation covered the centerline of the east-west township road, in line with fence south, and also the lost position (M&L) between section corners. Found nothing. Additional details regarding the dig can be found in the 2011 Remonumentation book.

7-9-2012 Having found no survey monuments, Joel Thoreson, County Surveyor, decided the centerline of road E-W in line with fence south is the best perpetuation of the original corner location. Olmsted County survey crew set a 5' telspar pipe with cast iron cap, down 0.7', at said location.