Certificate of Location of Government Corner

ID#: 830105 **Description:** SEC COR 1 2 11 12 83 **Date Set:** 7/9/2012 **County:** Olmsted

Section: 01 **Township:** 108N **Range:** 13W **Monument Description:** 1" square pipe with cap "42638"

Reference Ties:

The monument is down 0.1'
The corner falls in centerline of CSAH 11 and 1' south of centerline of township road east and in centerline of townshp road west.
This corner is located by GPS reference stations "Boots A & B"

Corner History:

1854 William Yerby; Set post to corner section 1,2,11,12 in mound of earth and sod. Deposited charcoal, made trench, pits, and planted osage orange seed NW & SE.

9-11-1979 County Surveyor dug from the traverse nail set in the center of the intersection, 3' East, 3' west, 4' north, and 6' south by 6 1/2' to 7' deep to clay. Didn't find anything.

8-28-1985 V. Fangman set pk nail at surface in centerline of CSAH 11 and in centerline of E-W twp road.

8-3-1993 County Surveyor found V. Fangman PK nail in good condition and referenced before road resurfacing.

7-8-1994 County Surveyor found and checked PK nail which was reset by county highway department at 1993 referenced location of V.Fangman PK nail. The PK nail falls 1/2' west of centerline CR#11 and 1' south of centerline twp road east & in centerline of twp road west.

3-20-2007 County Surveyor found pk nail at surface in good condition and located using GPS reference stations

6-2011 PK nail was destroyed by road resurfacing

7-9-2012 County survey crew set 1" square pipe, 2' long with cap "42638" at the previously measured PK nail location.