Certificate of Location of Government Corner

ID#: 830305 **Description:** SEC COR 3 4 9 10 83 **Date Set:** 7/6/2012 **County:** Olmsted

Section: 03 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is down 0.7'
The corner falls in the centerline of CR 128 and in the centerline of E-W township road
This corner is located by GPS measurement

Corner History:

1854 William Yerby; 80.0 set a section post for corner to sections 3-4-9-10 in mound of earth and sod. Made trench and pits, deposited charcoal & planted osage orange seeds on NE & SW sides of trench. RPs- 72.50 slough NE & SW, 74.50 leave slough NE & SW.

10-6-2011 County survey crew dug for the 1854 section post. The excavation was 10' x 12' with a depth of 7'. The excavation covered the centerline of the east-west township road (125th St. NE) and the centerline of the north-south county road (CR 128) and also covered a computed position by doubling the distance and projecting the line of the west line of the SW quarter of Section 3. Found nothing. Additional details regarding the dig can be found in the 2011 Remonumentation book.

7-6-2012 Having found no survey monuments, Joel Thoreson, County Surveyor, decided the intersection of roads E-W and N-S is the best perpetuation of the original corner location. Olmsted County survey crew set a 5' telspar pipe with cast iron cap, down 0.7', at said road intersection.