Certificate of Location of Government Corner

ID#: 831004 **Description:** 1/4 SEC COR 10 15 83 **Date Set:** 4/28/2003 **County:** Olmsted

Section: 10 **Township:** 108N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The monument is down 0.4'
The corner falls in centerline of TH 247
This corner is located by GPS measurement

Corner History:

1854 William Yerby; 39.89 set a quarter section post in mound of earth & sod. Made trench with pits and deposited charcoal and planted osage orange seed on east & west sides of trench.

5-1900 C.Armstrong Pg.667 No.593; Found boulder in center of road in line fences N & S. Accepted as corner.

7-21-1970 County Surveyor, centerline road cut. Corner lost.

10-8-2002 County Surveyor found nothing.

4-28-2003 County Surveyor set 1" square pipe w/cap at surface from computed data from GPS reference points. Monument falls in centerline of Mn/DOT #247.

5-26-2006 County Surveyor found 1" square pipe w/cap at surface in good condition.

3-12-2007 County Surveyor found 1" square pipe w/cap at surface in good condition.

4-30-2013 County survey crew found 1" square pipe with cap at surface in good condition. Lowered pipe and cap 0.4' in preparation for 2013 road overlay.