Certificate of Location of Government Corner

ID#: 831304 **Description:** 1/4 SEC COR 13 24 83 **Date Set:** 8/3/1983 **County:** Olmsted

Section: 13 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is up 0.1'
The corner falls on west side of CP to fences E-W-N and in line with fences E-W-N
Post 2' North
This corner is located by GPS measurement

Corner History:

5-1854 Gov't notes, William B. Yerby, Deputy Surveyor West on true line between sections 13 and 24. 40.045 chs. Set a quarter section post in mound of earth and sod. Deposited charcoal. Made a trench and pits. Planted Osage Orange seed N&S 80.09 chs. to section corner.

6-1867 H.E. Horton, Surveyor, (Book A, Page 85, No. 130) may have used this corner to set the Center 13.

11-1877 Thomas Hunter, County Surveyor, (Book A, Page 323, No. 317, and old Fieldbook 5, Page 26) "Found original mound with pits but stake missing, drove new stake in center of mound. He used the corner to set the 1/16 East, a stake, midway (19.97 chs.) and on line to E. Sec. Cor. 13-24, and to set the Center 24, a stake at intersecting 1/4 lines.

8-3-1983 County Surveyor dug at the corner post to fences E-W-N Found a 2 1/2"x4 1/2"x14" limestone leaning badly and too high in fill about post to be Hunter's corner (came .41 East and 2.03 south of final corner here). Dug 4' deep to clay. Found mark of old post running deep into clay which came at the intersection of the line from the S. 1/4 Cor. 24 (stone found) over stone standing by the corner post at the Center 24 and line from the E. Sec. Cor. 13-24 (a stone found) over stub of old post found at the 1/16 East, so accepted as Hunter's location and set a telspar pipe with Cast Iron Cap as the corner. Measured 1318.00' east to post stub found at the 1/16 east, then 1317.40' to the E.Sec. Cor. 13-24.

10-19-2011 County survey crew found cast iron cap in good condition.