Certificate of Location of Government Corner

ID#: 831306 **Description:** 1/4 SEC COR 13 14 83 **Date Set:** 7/28/1983 **County:** Olmsted

Section: 13 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.8'
The corner falls 6' east of centerline of N-S twp road and in line of fences east and west
County Survey Disk in CP W 39.22'
County Survey Disk in fence post E 67.74'
County Survey Disk in PP #2665 NNE 61.13'
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes William Yerby, Deputy Surveyor North between sections 13 and 14. 40.00 chs. Set a quarter section post in mound of earth and sod. Deposited charcoal. Made trench and pits. Planted Osage Orange seed E & W.

6-1867 H.E. Horton, Surveyor, (Book A, Page 85, No. 130) may have used this corner (no description) to set the Center 13. Measured north 39.76 chs. To Sec. Cor. 11-12-13-14 and measured 39.21 chs. To the Center 13.

10-1875 Thomas Hunter, County Surveyor, (Book A, Page 406, No. 395, and old Field book 14, Page 58) surveyed lots in Potsdam in the NE1/4 Sec. 14. (Also old Field book 4, Page 76)

4-1877 Thomas Hunter surveyed lots in Potsdam in the NW1/4 Sec. 13. (Book A, Page 406, No. 395, and Old Field book 14, Page 58, and old Field book 4, Page 77). He shows a stake at 1/4 Cor. 13-14 and a measure of 39.76 chs. north to Sec. Cor. 11-12-13-14.

9-1894 Thomas Hunter, County Surveyor, (Book A, Page 552, No. 509) "Found boulder stone that Mr. C. Schultz said he and Mr. Schacht put in place of stake that was put in by Thomas Hunter as 1/4 S. Left as found". He used the corner to set the Center 14, a square block, at intersecting 1/4 lines which came just 2 1/2 lks. west of the corner post of the fence running east there.

7-28-1983 County Surveyor dug for this corner with the backhoe in the N-S road. Found pieces of bone and glass in black mark in clay. Dug down and found pieces of charred wood and a deep stake hole at north side of mark. Stone possibly stood over glass and black mark and is now gone. Drove 3' drill steel in stake hole as corner. Also dug for the Center 14 but did not find Fraser's square block; however, the Center would come at the center of 3 corner post fence corner there. Measured north 2625.98 to Sec. Cor. 11-12-13-14.

8-3-1983 County Surveyor set a Cast Iron Monument over the 3' long drill steel driven in stake hole 7-28-1983. Corner is in line with fences east and west, and is 6' east of the center of the N-S road here.

9-7-2010 County survey crew found CIM in good condition.