Certificate of Location of Government Corner

ID#: 831404 **Description:** 1/4 SEC COR 14 23 83 **Date Set:** 7/27/1983 **County:** Olmsted

Section: 14 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is up 0.1'
The corner falls 1' north of CP to fences N-S-E
Spike in W side CP S 1.01'
Spike in N side brace post ESE 9.44'
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes William B. Yerby, Deputy Surveyor West on true line between sections 14 and 23. 40.00 chs. Set a quarter section post in mound of earth and sod. Deposited charcoal. Made trench and pits. Planted Osage Orange seed N & S 80.00 chs. to section corner.

9-1894 William C. Fraser, County Surveyor, (Book A, Page 552, No. 509) "found stone planted as corner and left as found, said stone was planted by Mr. G. Renike. Mr. H. Schacht & Mr. Schultz, and Mr. G. Renike. Mr. H. Schacht said that the mound was still there when they planted the stone. " He used this corner to set the Center 14, a square block at intersecting 1/4 lines.

7-27-1983 County Surveyor dug at the corner post to fences N-S-E. Found a 14"x17"x26" pointed boulder, top down 16" and dug well down into clay. There was a 10"x10" square black mark in the clay on the East side of the stone. Found nothing further. Set a telspar pipe with a cast iron cap as the corner at the stone location and set the stone on the East side of the pipe. Also dug for the Center 14 but did not find Fraser square block; however, the Center would come at the center of 3 cornerpost fence corner there.

10-19-2011 County survey crew found cast iron cap in good condition.