Certificate of Location of Government Corner

ID#: 831506 **Description:** 1/4 SEC COR 15 16 83 **Date Set:** 4/28/2003 **County:** Olmsted

Section: 15 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 3' west of centerline of N-S twp road and in line with common farm line west
This corner is located by GPS reference stations "Culbertson A & B"

Corner History:

5-1854 Gov't Notes: William Yerby, 40.00 set a quarter sec post in mound of earth and sod. Made trench and pits. Deposited charcoal and planted Osage Orange seed on E and W sides of trench.

5-1900 Ch. Armstrong P.667 No.593 S.15. A. Kruger found burr oak stake 3' deep in wash fill in road 3" wide 28" long. Accepted this as corner and set stone 12x18x30. Meas north and south mile 79.98.6. No mention of section corners only that E and W temp points set P.666 observed.

10-16-2002 County Surveyor set 2 points to GPS, did not try to locate stone.

4-28-2003 County Surveyor set 4' telspar w/Cast Iron Cap down 0.5'. Monument falls 3.0' West of centerline of 50th Ave NE and seems to fall in line with common farm line to the West and in line with tree 1/2 mile West. Monument set by computed data from GPS reference points.

9-13-2011 County survey crew found cast iron cap in good condition.