Certificate of Location of Government Corner

ID#: 831705 **Description:** SEC COR 17 18 19 20 83 **Date Set:** 6/9/2000 **County:** Olmsted

Section: 17 **Township:** 108N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 1/2' east of centerline of TH 63 and 1 1/2' north of centerline of twp road west
Punch mark in N end CMP NW 44.06'
County Survey Disk in CP (on East side of old one) E 75.60'
Punch mark in S end CMP SW 44.54'
County Survey Disk in PP SW 88.28'
Ref pipe W 82.79'
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes William B. Yerby, Deputy Surveyor North between sections 19 and 20. 80.00 chs. Set a charred section post in mound of Earth and Sod for corner to sections 17, 18, 19 & 20, and made trench and pits, and planted Osage orange seed on N.E. and S.W. sides of trench.

1-1878 Thomas Hunter (P. 327 No. 321), County Surveyor, did not look for the corner but a William Blohm avers he and others set a stone where the old stake stood.

5-1878 T. Hunter (P. 346 No. 339) found stone P.327.

5-1878 T. Hunter (P. 347 No. 340) found stone P. 346. Set stone at 1/4 Cor. 17-18 midway and on line.

6-1879 T. Hunter (P. 361 No. 352) found stone P. 346.

4-1919 Charles Armstrong (P. 318B), County Surveyor, found a 5"x12"x13" boulder.

5-23-1976 County Surveyor found corner comes in a deep cut area of T.H. 63. Reset the corner at double the line and measure from Sec. Cor. 7-8-17-18 (found) over 1/4 Cor. 17-18 (found) as per Hunter's survey No. 340. Set a C.I.M. over a 1-1/4" x 12" pipe as the corner.

7-26-1999 County Surveyor found CIM in good condition. Set ref pipe and tied out corner.

6-9-2000 County Surveyor set 1" square pipe w/cap at surface from 1999 tie out.

3-12-2007 County Surveyor found 1" square pipe w/cap at surface in good condition.