Certificate of Location of Government Corner

ID#: 831804 **Description:** 1/4 SEC COR 18 19 83 **Date Set:** 6/2/76 **County:** Olmsted

Section: 18 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.6'
The corner falls 7' south of centerline of E-W twp road, 17 1/2' east of centerline of driveway north and 4' west of fence south
County Survey Disk in CP NW 57.00'
County Survey Disk in CP NNE 37.24'
County Survey Disk in PP #43573 SE 55.77'
Post with sign, south southeast 25'
This corner is located by GPS measurement

Corner History:

5-15-1854 Gov't Notes William B. Yerby, Deputy Surveyor East on true line between sections 18 and 19. 37.20 chs. Set a charred quarter section post in mound of sod. Made trench and pits and planted Osage orange seed on east and west sides of trench. 77.20 chs. To secion corner.

1-1878 Thomas Hunter (P. 327 No. 321), County Surveyor, found old stake remains. Set stone 3"x5" /12"x 23" as corner.

6-1879 T. Hunter (P.361 No. 352) found stone P.327. Set a stone at the 1/16th north midway and on line to a stone set at the Center of Section 18.

5-20-1976 County Surveyor doubled line and measure from Center Section 18 (found) over the 1/16th south (found) and dug with backhoe. Road had been cut in recent grading. Found remaining 12" of recorded stone lying flat but could not identify the spot where it stood.

6-2-1976 County Surveyor set C.I.M. over a shaft and pipe as the corner at the intersection of the N-S 1/4 line of Section 18 and the line from the S.W. Corner 18 to the S.E. Corner 18.

9-10-2010 County survey crew found CIM in good condition.