Certificate of Location of Government Corner

ID#: 831806 **Description:** W 1/4 SEC COR 18 83 **Date Set:** 6/2/1976 **County:** Olmsted

Section: 18 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' south of E-W fence and 1' west of N-S fence
Post w/sign 2' east
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor, North between sections 13 and 18. 40.00 chs. Set post and drove charred stake for quarter section corner. Built mound with trench per instructions. Planted S.E. Osage orange, N.E. apple seed.

6-1878 Thomas Hunter (Old Field Book#5, P. 72), County Surveyor, found the original post in mound by the side of the fence post. Used the corner to set the Center of Section 18.

6-1879 Hunter (P. 361 No. 352), County Surveyor, found the original stake standing in mound.

6-2-1976 County Surveyor set a C.I.M. over a pipe as the corner at the intersection of the line from the E. 1/4 Cor. 18 (found) over the Center 18 (found) and the line from the S.W. Cor. Sec. 18 to the W. 1/4 Cor. Sec. 7.

10-11-2005 County Surveyor found CIM in good condition down 0.3'. Monument falls 5'± west of lone wood post, owner took out line fences and surrounded by cultivated on all but SE sides. Set sign & post 2.0' east.