Certificate of Location of Government Corner

ID#: 831904 **Description:** 1/4 SEC COR 19 30 83 **Date Set:** 5/28/1976 **County:** Olmsted

Section: 19 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 1'.
This corner is located by GPS measurement.

Corner History:

1854 Gov't Notes William Yerby, Deputy Surveyor
Course N89º 39'E on true line between sections 19 and 30. 37.40 chs. Set a quarter section post in mound of earth and sod, deposited charcoal, made trench and pits, and planted Osage orange seed North and South.

1-1878 Thomas Hunter (P.327 No.321), County Surveyor, could not find corner. Measured South line of Section 19 and set a stake at proportionate Gov't measure.

3-1879 T. Hunter (P. 355 No. 347) found stake set P. 327.

10-1965 John Kerr (Book 90 P. 58), County Surveyor, measured South line of Section 19.

4-1-1976 County Surveyor dug 5' x 5' x 3' deep but found nothing. Diggings covered location of corner of proportionate Gov't measure, by doubling line and measure of corner post found at 1/16W, and also by intersecting the line from the corner post at the 1/16S of the Center 30 over the corner post at the Center 30 with the North line of Section 30.

5-28-1976 County Surveyor set a C.I.M. over a 1-1/4"x24" pipe on line and at proportionate Gov't measure as per Hunter.

9-10-10 County survey crew found CIM in good condition. The area has been cleared for cropland and all fences are gone.