Certificate of Location of Government Corner

ID#: 831906 **Description:** W 1/4 SEC COR 19 83 **Date Set:** 5/18/1976 **County:** Olmsted

Section: 19 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

County Survey Disk in CP N 201.15' (?)
Post w/sign 1' SSW
This corner is located by GPS reference stations "Wilder C & D"

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor
North between sections 19 and 24. 40.00 chs. Set post and drove charred stake for quarter section corner. Built mound with trench per instructions. Planted S.E. Osage, orange N.E. apple seed.

5-1877 Thomas Hunter (P. 308 No. 302), County Surveyor, could find no corner. Set stone 4"x6"x24" midway and on line.

1-1878 T. Hunter (P.327 No. 321) found stone P. 308.

5-18-1976 County Surveyor dug and found 4"x6"x approx. 18" limestone 2-1/2' deep. Drove pipe on the North side and a rod on the South side of the stone. Set a C.I.M. over the stone with a steel post on the N.W. side of the C.I.M.

10-11-2005 County Surveyor found CIM in good condition down 0.3'. 1 1/4' pipe on east side, steel post on north side. Sign & post on SSW side.

11-2-2005 County Surveyor found CIM down 0.3' in good condition. Cut down large boxelder to the east. Set sign and post 1.0' SSW. Updated all ties except for CSD in corner post.