Certificate of Location of Government Corner

ID#: 831909 **Description:** SEC CEN 19 83 **Date Set:** 9/21/1999 **County:** Olmsted

Section: 19 **Township:** 108N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" pipe w/cap RLS #14888

Reference Ties:

The monument is at the surface.
The corner falls 3.5' east of N-S fence and 2' north of E-W fence
The corner is located by GPS measurement

Corner History:

1-17-1878 T. Hunter P.327 No.321 set marked stake at true inters lines. 16 east set stake M&L 19.91. 16 south set stake M&L 19.95-1/4. 16 center SE 1/4 19 set stake inters 1/16 lines.

4-1919 Ch. Armstrong P.318B set iron stake at center and iron bolt at 1/16 corner east of center 1311' on line iron bolt set as 1/4 19-20, claims corner on E-W 1/4 line as being iron bolt set by Hunter (no record of it). Plat shows iron bolts at center 19 and E 1/4 19 and 1/16 corner between all 1311.0' typical Armstrong.

2-10-1976 County Surveyor set nail at comp location near center (see drwg). RP's: Nail N side of corner post WSW 5.15, location 1.6' N of fence east.

3-31-1976 County Surveyor dug 2'x6'x1-1/2' deep on N side of fence E from corner post. Found nothing.

5-20-1976 County Surveyor dug 3' diameter 4' deep. Found stake deep in old post .8 N and .8 W of traverse nail. Set wood post in hole and small rod over. RP's: Nail in corner post SW 4.6 2.35 N of fence E.

9-21-1999 Vince Fangman set 1/2" pipe w/cap #14888 at intersecting quarter lines.

9-30-2010 County survey crew found 1/2" pipe in good condition