Certificate of Location of Government Corner

ID#: 832006 **Description:** 1/4 SEC COR 19 20 83 **Date Set:** 5/27/1976 **County:** Olmsted

Section: 20 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 38' east of CP to fences east-west-north
The monument is at the surface
County Survey Disc in S side CP W 38.00'
County Survey Disc in 8" Cedar ESE 25.15'
The corner is located by GPS measurement

Corner History:

5-24-1854 William B. Yerby, Deputy Surveyor, measured north 40.00 chains between Sections 19 and 20. Set charred quarter post in mound of earth and sod. Made trench and pits, and planted Osage Orange seed on east sides of trench.

1-17-1878 Thomas Hunter, County Surveyor, (Book A, Page 327, Survey No. 321), found stake unmarked in the center of mound, but pits obliterated, but line of old fences running north, east and west.

5-28-1878 Thomas Hunter, County Surveyor, (Book A, Page 346, Survey No. 339), found stake in mound.

4-29-1919 Charles Armstrong, County Surveyor, (Book B, Pages 318-319), could not find corner. Set an iron bar as corner at the intersection of the E-W 1/4 line of Section 19 and a line from the NE Corner Section 19 to the east edge of a large ash tree averred by those present as being just west of the section line south of the SE Corner Secion 19. RP - 9" Birch N9°E 74'

3-31-1976 County Survey Crew found Armstrong's 1" iron under east-west fence.

5-27-1976 County Survey Crew lowered 1" iron and set Cast Iron Monument at the surface over iron. RPs - County Survey Disc in S side CP W 38.00', County Survey Disc in 8" Cedar ESE 25.15'.

9-10-2010 County Survey Crew found Cast Iron Monument at surface in good condition and measured its position using GPS.