Certificate of Location of Government Corner

ID#: 832206 **Description:** 1/4 SEC COR 21 22 83 **Date Set:** 6/8/1966 **County:** Olmsted

Section: 22 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of north-south township road (50th Ave NE) and 1' north of fence west
The monument is down 1'
County Highway Disc in west side PP NNE 108.58'
County Highway Disc in top corner fence post E 33.9'
County Highway Disc in top corner fence post W 32.9'
This corner is located by GPS measurement

Corner History:

5-19-1854 William B. Yerby, Deputy Surveyor, measured north 40.00 chains between Sections 21 and 22. Set quarter section post in mound of earth and sod, deposited charcoal. Made trench and pits, planted Osage Orange seed on east and west sides of trench.

5-7-1900 Charles Armstrong, (Book A, Page 666, Survey No. 592), set 3"x10"x18" limestone midway and on line at 39.993 chains.

9-13-1962 John Kerr, County Surveyor, (Book C, Page 110 and Kerr Field Book 86, Page 9), dug completely across road 4' wide no bad wash or fill or near hillocks. Question as to whether corner ever was set. After establishing NE Section Corner 21, set 1/2"x48" rod midway and on line at 2632.85'. The corner falls in centerline of road and 1' north of fence west. RPs - Disc in west side PP NNE 108.58'. Disc in top corner post E 33.9', Disc in top corner post W 32.9'.

6-8-1966 John Kerr, County Surveyor, could not find corner. Set Cast Iron Monument over 1/2"x24" rod midway and on line.

9-10-2010 County Survey Crew found Cast Iron Monument down 1' in good condition and measured its position using GPS.