Location of Center of Section

ID#: 832409 **Description:** SEC CEN 24 83 **Date Set:** **County:** Olmsted

Section: 24 **Township:** 108N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Stone

County Surveyor recommends using the computed intersection of quarter lines for the center of section.

Reference Ties:

The corner falls in line with fences east, west, and south
The monument is up 0.5'
This corner is located by GPS measurement

Corner History:

11-8-1877 Thomas Hunter, County Surveyor, (Book A, Page 323, Survey No. 317), set stake at intersecting quarter lines. 1/16th East set stake midway and on line at 19.95-3/4 chains (1317.20').

7-7-1983 County Survey Crew found 4" square topped stone standing on north side of corner post to fences east-west-south. Roger Brand, County Surveyor, used center to set 1/4 Corner 23-24 and 1/4 Corner 13-24.

9-28-2010 County Survey Crew found stone up 0.5' in good condition and measured its position using GPS.

10-2-2014 Joel Thoreson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the stone monument, as located by GPS in 2010, falls 0.01' north and 0.09' east of the computed center.

2-8-2025 Eric Stennes, County Surveyor, used computed center at intersecting quarter lines for Olmsted County Highway Right of Way Plats No. 268 and 269.