Certificate of Location of Government Corner

ID#: 832605 **Description:** SEC COR 26 27 34 35 83 **Date Set:** 7/14/1994 **County:** Olmsted

Section: 26 **Township:** 108N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 1' east of centerline of CSAH 11 and in centerline of E-W twp road
The monument is down 0.8'
Punch hole in N end 20" CMP NW 37.89'
Punch hole in S end 20" CMP SW 37.20'
County Survey Disk in PP #19853 NE 59.58'
Ref pipe ENE 129.48'
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes William B. Yerby Deputy Surveyor north between sections 34 and 35. 80.00 chs. Set post in mound of earth and sod to corner to section 26, 27, 34, 35 deposited charcoal. Made trench and pits planted Osage orange seed NW and SE.

11-1877 Thomas Hunter County Surveyor (p. 324 No. 318) found stone planted at center of cross roads by Mr. Lindsley where original stake stood. Measured south 40.05 chains to 1/4 corner 34-35.

6-17-1930 County Highway Department (Book 58 pgs. 8, 35) found corner stone limestone on end 0.4' west of line run for road. Measured 2638.4' south to stone at 1/4 corner 34-35.

10-1946 John Kerr County Surveyor (Kerr Book 32, pages 27, 28, 29) shows "Stone with pipe and wagon skein on top" at corner. He used the corner to set 1/4 corner 26-35, a 1-1/4" x 4' iron pipe, midway (2630.35) and on line between the section corners. He also set the West 1/4 corner 26 a 3/8" x 3' pipe with 3/4" pipe on top, midway (2643.71') and as line to the NW corner of 26, a 1" shaft 2' long, also set this survey (no method).

1953 County Highway Department (Book 199 p. 4) shows "steel pipe and stone" at corner. Measured south 2636.5' to limestone at 1/4 corner 34-35.

8-1-1961 County Highway Department (Book 199 p. 4) "Placed drill rod".

6-14-1983 County Surveyor found County Highway Department drill rod, 7-5-83 dug at section corner 26,27, 34, 35 found drill rod to be 10" long. Down 12" found a 3' drill rod .36' north and .01' east. Down 2' found 1" pipe in wagon skein .24' north and .03' east. Down 3.3' found 3 1/2"x9"x14" limestone and remaining 9" of a 2" diameter stake.

7-30-1993 County Surveyor set 1" square pipe w/cap angle Rt 180° 01' 06" to P.K. nail in PP ENE of corner 2nd pole on N side of road east. The Ref. pipe is ± 10' N of centerline E-W Twp Rd and ± 128 east of centerline CR #11. Angle at Ref. pipe to sec cor 26-27-34-35, VA 90° 39' 08" slope 129.49' Hor 129.48'.

7-14-1994 County Surveyor set 1" square pipe w/cap at 1993 referenced location. The corner is 1' east of centerline CR #11 and in centerline of Twp Rd east and west.

3-12-2007 County Surveyor found 1" square pipe w/cap at surface in good condition.

5-24-2011 County survey crew found 1" sq. pipe with cap in good condition. Drove pipe down below bituminous in preparation for road surface milling and overlay.