Location of Center of Section

ID#: 832609 **Description:** SEC CEN 26 83 **Date Set:** 10/15/1946 **County:** Olmsted

Section: 26 **Township:** 108N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

1-1/4" iron pipe

County Surveyor recommends using the computed intersection of quarter lines for the center of section.

Reference Ties:

The corner falls 0.5' SW of corner post to fences north, south, and west
The monument is down 0.3'
This corner is located by GPS measurement

Corner History:

10-15-1946 John Kerr, County Surveyor, (Book C, Page 50 and Kerr Field Book No. 32, Page 28), Set 1-1/4"x4' iron pipe at intersecting quarter lines.

5-8-1962 John Kerr, County Surveyor, (Book C, Page 14 and Kerr Field Book No. 85, Page 31), found and used 1-1/4" iron pipe.

8-2-1983 County Survey Crew found 1-1/4" pipe on SW side of corner post to fences north, west, and south. Remains of old corner post 1.5' east as described by John Kerr.

4-26-2005 Vince Fangman used computed center at intersecting quarter lines.

9-20-2010 County Survey Crew found 1-1/4" pipe down 0.3' in good condition and measured its position using GPS.

10-2-2014 Joel Thoreson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the 1-1/4" pipe, as located by GPS in 2010, falls 1.12' south and 1.17' east of the computed center.

2-8-2025 Eric Stennes, County Surveyor, used computed center at intersecting quarter lines for Olmsted County Highway Right of Way Plats No. 266 and 267.