Certificate of Location of Government Corner

ID#: 832704 **Description:** 1/4 SEC COR 27 34 83 **Date Set:** 10/10/1972 **County:** Olmsted

Section: 27 **Township:** 108N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.6'
The corner falls 1' north of centerline of E-W twp road and 2' west of fence south
Top corner iron post NW 31.19'
1/2" rod under fence south SSE 70.0'
Pepsi cap in S side PP #19881 NE 70.95'
Punch hole in W end CMP NNE 23.62'
This corner is located by GPS measurement

Corner History:

1854 William Yerby; 39.96 set a quarter section post in mound of earth & sod, deposited charcoal, made trench with pits, and planted osage orange seed N & S.

11-1877 T. Hunter, Pg.324 No.318; Found stake in center of road on range of N-S fences.

10-1893 W.Fraser Pg.536 No.498; Found Hunter stake Pg.324 in center of road. Set stone 4x8x24 in place of stake. Meas. West to stone set.

10-1972 County Surveyor found limestone shattered some. Set old lawn mower frame case with top of stone where motor was bolted with 5/8"x11" rod and glass. RPs- 2' east to fence south, 1.5 south to center road, 70.0 2' east of south to 1/2"' rod under fence running south, 70.76' NE to pepsi cap on E side pp# 19881, 31.29' west of north to edge 2" angle post top, 23.54' NE to punch hole in west end 15" field drive culv.

6-15-1983 County Surveyor found CIM down 0.3' in E-W road, 1' north of centerline and 2' west fence line south. RPs' pepsi cap on south side pp# 19881 NE 70.95', punch hole top west end CMP in field drive NNE 23.62', top corner iron post NW 31.19'.

9-10-2010 County survey crew found CIM in good condition.